

Xantrex™ Trace Series Inverter/Charger

Electrical Specifications								
Part number	989-1000	989-1010	989-1005	989-1015	989-1020	989-1025	989-1030	989-1035
Model number	TR1512-120-60	TR2412-120-60	TR1524-120-60	TR2424-120-60	TR3624-120-60	TR1512-230-50	TR1524-230-50	TR2424-230-50
Invert mode:								
Waveform	Modified sine wave	Modified sine wave	Modified sine wave	Modified sine wave	Modified sine wave	Modified sine wave	Modified sine wave	Modified sine wave
Continuous output power	1500 VA	2400 VA	1500 VA	2400 VA	3600 VA	1500 VA	1500 VA	2400 VA
AC output voltage (rms)	120 Vac	120 Vac	120 Vac	120 Vac	120 Vac	230 Vac	230 Vac	230 Vac
AC output frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	50 Hz	50 Hz	50 Hz
Rated AC output current	12.5 Aac	20 Aac	12.5 Aac	20 Aac	30 Aac	6.5 Aac	6.5 Aac	10.4 Aac
Surge capability Max. Output & Duration:								
Overload 10 sec rating	3000 VA	4800 VA	3000 VA	4800 VA	7200 VA	3000 VA	3000 VA	4800 VA
Short Circuit 10 sec rating	50±5 Apk	80±8 Apk	50±5 Apk	80±8 Apk	120±12 Apk	26.5±2.5 Apk	26.5±2.5 Apk	42±4 Apk
Adjustable load sensing range	5 watts minimum to 240 watts maximum					10 watts minimum to 480 watts maximum		
DC input current at no load - search mode	0.35 amps	0.35 amps	0.17 amps	0.17 amps	0.20 amps	0.35 amps	0.20 amps	0.20 amps
Efficiency - peak	> 90%	> 92%	> 92%	> 93%	> 94%	> 92%	> 91%	> 94%
DC input voltage range	11.0 - 15.0 Vdc	11.0 - 15.0 Vdc	22.0 - 30.0 Vdc	22.0 - 30.0 Vdc	22.0 - 30.0 Vdc	11.0 - 15.0 Vdc	22.0 - 30.0 Vdc	22.0 - 30.0 Vdc
Rated DC input current	157 amps	252 amps	76 amps	120 amps	186 amps	158 amps	77 amps	121 amps
Load power factor (allowed)	0.8 to 1.0 (leading or lagging)					0.8 to 1.0 (leading or lagging)		
Series operation	Yes - Two units can be connected to produce 120/240 Vac split phase power, stacking cable included					No	No	No
Bypass / Charge mode:								
AC input voltage range	65 - 140 Vac (wide), 95 - 140 Vac (narrow)					120 - 253 Vac (wide), 180 -253 Vac (narrow)		
AC input frequency range	55 - 64 Hz (narrow-charge & pass-through), 55 - 68 Hz (wide-charge), 41 - 68 Hz (wide pass-through)					45 - 55 Hz (narrow-charge & pass-through), 45 - 68 Hz (wide-charge), 41 - 68 Hz (wide pass-through)		
Built-In internal supplemental breakers	30 Aac bypass, 20 Aac charger	30 Aac bypass, 30 Aac charger	30 Aac bypass, 20 Aac charger	30 Aac bypass, 30 Aac charger	30 Aac bypass, 30 Aac charger	15 Aac bypass, 8 Aac charger	15 Aac bypass, 8 Aac charger	15 Aac bypass, 15 Aac charger
DC charger rate (adjustable)	10 - 70 amps	14 - 100 amps	5 - 35 amps	10 - 70 amps	10 - 70 amps	10 - 70 amps	5 - 35 amps	10 - 70 amps
AC input current at max. charge rate	11.2 Aac	15.8 Aac	10.2 Aac	19.7 Aac	19.5 Aac	5.9 amps	6.0 amps	10.4 amps
AC input power factor	0.88	0.89	> 0.88	0.92	0.93	0.91	> 0.83	0.92
Multi-stage charging	Yes - bulk, absorption and float, plus user-initiated equalize (for flooded batteries only)					Yes - bulk, absorption and float, plus user-initiated equalize (for flooded batteries only)		
Temperature compensation	Battery temperature sensor included					Battery temperature sensor included		
Automatic transfer relay	30 amps	30 amps	30 amps	30 amps	30 amps	15 amps	15 amps	15 amps
Transfer time (typical)	< 40 ms (wide), < 20 ms (narrow)					< 40 ms (wide), < 20 ms (narrow)		
Environmental Specifications								
Dimensions (W x H x L)	8.5 x 7.25 x 21" (216 x 184 x 546 mm)							
Weight	40 lbs (18 kg)	42 lbs (19 kg)	40 lbs (18 kg)	45 lbs (20 kg)	45 lbs (20 kg)	42 lbs (19 kg)	42 lbs (18 kg)	42 lbs (20 kg)
Shipping Dimensions (W x H x L)	12.4 x 11.8 x 26.6" (315 x 300x 675 mm)							
Shipping Weight	50 lbs (22.7 kg)	52 lbs (23.6 kg)	50 lbs (22.7 kg)	55 lbs (24.9 kg)	55 lbs (24.9 kg)	52 lbs (23.6 kg)	52 lbs (23.6 kg)	52 lbs (23.6 kg)
Operating temperature range	0 °C to +50 °C	0 °C to +50 °C	0 °C to +50 °C	0 °C to +50 °C	0 °C to +50 °C	0 °C to +50 °C	0 °C to +50 °C	0 °C to +50 °C
Mounting	Wall-mount (with 16" mounting centers)					Wall-mount (with 16" mounting centers)		
Warranty	Two years	Two years	Two years	Two years	Two years	Two years	Two years	Two years

Regulatory Approvals
CSA Certified to CSA 107.1, UL1741, FCC Class B and Industry Canada, CE

Specifications subject to change without notice.